

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
 Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
 Email: sales@cargoequipmentsolutions.com

Diesel Generating Set C125

MODEL	C125
Standby Power (60Hz)	110KW / 138KVA
Prime Power (60Hz)	100KW / 125KVA

Standard Features

General Features:

- Engine (DCEC Cummins 6BT5.9-G2)
- Radiator 50C max, fans are driven by belt, with safety guard
- 24V charge alternator
- Alternator: single bearing alternator IP23, insulation class H/H
- Absorber
- Dry type air filter, fuel filter, oil filter
- Main line circuit breaker
- Standard control panel
- Two 12V batteries, rack and cable
- Ripple flex exhaust pipe, exhaust siphon, flange, muffler.
- User manual.




PHOTO FOR REFERENCE ONLY

Generator Ratings

Voltage	HZ	Phase	P.F (COS φ)	Standby Amps	Standby Ratings (KW/KVA)	Prime Ratings (KW/KVA)
480/277	60	3	0.8	165	110/138	100/125
460/266	60	3	0.8	172	110/138	100/125
440/254	60	3	0.8	180	110/138	100/125
416/240	60	3	0.8	190	110/138	100/125

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Sales Promises

Cargo Equipment Solutions, Inc provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty on equipments are: One (01) year or 1000 Hours of standard working condition, what ever comes first. Service and parts are available from Cargo Equipment Solutions, Inc.

Specifications may change without notice.

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
Email: sales@cargoequipmentsolutions.com

Diesel Generating Set C125

ENGINE DATA

Manufacturer / Model:	DCEC Cummins 6BT5.9-G2, 4-cycle
Air Intake System:	Turbo
Fuel System:	AD type fuel pump
Cylinder Arrangement:	6 in line
Displacement:	5.9L
Bore and Stroke:	102*120 (mm)
Compression Ratio:	17.0 : 1
Rated RPM:	1800rpm
Max. Standby Power at Rated RPM:	130KW / 176Hp
Governor Type:	Electronic

Exhaust System

Exhaust Gas Flow:	19.4 m3/min.
Exhaust Temperature:	570°C
Max Back Pressure:	10kPa

Air Intake System

Max Intake Restriction:	6.35 kPa
Burning Capacity:	9.1m3/min
Air Flow:	210m3/min

Fuel System

100%(Prime Power) Load:	24.82 Lts / Hr
75%(Prime Power) Load:	24.94 Lts / Hr
50%(Prime Power) Load:	25.76 Lts / Hr

Oil System

Total Oil Capacity:	16.3L
Oil Consumption:	≤4g/Kwh
Engine Oil Tank Capacity:	14.2L
Oil Pressure at Rated RPM:	345kPa

Cooling System

Total Coolant Capacity:	29 L
Thermostat:	82-95°C
Max Water Temperature:	104°C

Specifications may change without notice.

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
Email: sales@cargo equipmentsolutions.com

Diesel Generating Set C125

ALTERNATOR SPECIFICATION

General Data

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34-1, CSA22.2 and AS1359 standards.

Alternator Data

Number of Phase:	3
Connecting Type:	3 Phase and 4 Wires, ΔY_j type connecting
Number of Bearing:	1
Power Factor:	0.8
Protection Grade:	IP23
Altitude:	$\leq 1000\text{m}$
Exciter Type:	Brushless, self-exciting
Insulation Class, Temperature Rise:	H/H
Telephone Influence Factor (TIF):	< 50
THF:	$< 2\%$
Voltage Regulation, Steady State:	$\leq \pm 1\%$
Alternator Capacity:	137.5 KVA
Alternator Efficiencies:	90.80%
Air Cooling Flow:	0.617m ³ /s

GENERATING SET DATA

Voltage Regulation:	$\geq \pm 5\%$
Voltage Regulation, Stead State:	$\leq \pm 1\%$
Sudden Voltage Warp (100% Sudden Reduce):	$\leq +25\%$
Sudden Voltage Warp (Sudden Increase):	$\leq -20\%$
Voltage Stable Time (100% Sudden Reduce):	$\leq 6\text{S}$
Voltage Stable Time (Sudden Increase):	$\leq 6\text{S}$
Frequency Regulation, Stead State:	$\leq 5\%$
Frequency Waving:	$\leq 0.5\%$
Sudden Frequency Warp (100% Sudden Reduce):	$\leq +12\%$
Sudden Frequency Warp (Sudden Increase):	$\leq -10\%$
Frequency Recovery Time (100% Sudden Reduce):	$\leq 5\text{S}$
Frequency Recovery Time (Sudden Increase):	$\leq 5\text{S}$

Specifications may change without notice.

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
 Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
 Email: sales@cargoequipsolutions.com


Diesel Generating Set C125

Options

Engine	Fuel System	Control System
<ul style="list-style-type: none"> <input type="checkbox"/> Heater 2KW & 4KW <input type="checkbox"/> Battery Charger 3.5A & 7A 	<ul style="list-style-type: none"> <input type="checkbox"/> Daily Fuel Tank <input type="checkbox"/> Water Separator <input type="checkbox"/> Fuel Level Sensor 	<ul style="list-style-type: none"> <input type="checkbox"/> Remote Control Panel <input type="checkbox"/> Auto Transfer Switch (ATS) <input type="checkbox"/> Paralleling System
Alternator	Others	Data
<ul style="list-style-type: none"> <input type="checkbox"/> Anti Condensation Heater <input type="checkbox"/> Permanent Magnet Gen. <input type="checkbox"/> Drop CT (For Paralleling) 	<ul style="list-style-type: none"> <input type="checkbox"/> Rainproof Type <input type="checkbox"/> Soundproof Type <input type="checkbox"/> Trailer Type 	<ul style="list-style-type: none"> <input type="checkbox"/> Engine Parts Drawing List <input type="checkbox"/> Spare Parts


Dimensions & Weight

Open Type with Base Fuel Tank



Overall Size: 2230 (mm) *830 (mm) *1490 (mm)
 Weight: 1500kg

Soundproof Type



Overall Size: 3230 (mm) *1150 (mm) *1780 (mm)
 Weight: 1950kg

Specifications may change without notice.

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
Email: sales@cargoequipmentsolutions.com

Diesel Generating Set C125

Standard Control Panel



Cargo Equipment Solutions, Inc. Standard Control Panel is the basic configuration for normal operation and usage, it is a kind of intelligent controller with LED displaying the operating mode of the controller and the running state of the generator sets. It can configure the control procedure and protection parameter of the generator, and completely satisfied the automatic controlling requirement of different generator sets for the user or factory.

Auto Module Control Panel



Auto Module Control Panel is the configuration for nobody on duty controlling generators. This kind of panel adopts auto module control system, with large LCD display to show the menu.

Features: MRS10-can receive remote output signal from ATS and realize auto start and stop of generators.

MRS16-can realize all functions of MRS10, add RS232 interface which can communicate with PC to realize remote operation.

AMF25-Auto Mains Failure controller, can realize all functions of MRS16, furthermore can detect ATS and control directly.

Auto Parallel Control Panel



Automatic Parallel Control Panel, This new automatic parallel system adopts intelligent modules, inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined together with the generator, which is very reliable. One generator, one panel. The panel can be used both for singly and parallel. It is only need to parallel generator with such panel when the capability needs to be enlarged in the future.

Specifications may change without notice.